

Print Labels Anywhere, Anytime

LP 46 Dlite Label Printer



Compact and durable design



6" IPS printing speed



Increased storage
Flash 16 MB & SDRAM 32 MB



Interface: Standard USB port
Optional: Ethernet, Serial,
Bluetooth or Wifi



High ribbon capacity of 300 M

Applications



Retail



Warehouse



Factory



Logistics

Specifications



Print method	Thermal transfer
Resolution	203DPI
Print width	108mm(Max.)
Print speed	152mm/s(Max.)
Memory	SDRAM: 32MB, Flash:16MB (64MB optional)
Sensor	Photoelectric sensor
TPH temperature detection	Thermistor
TPH position detection	Microswitch
Interface	Standard USB port Optional: RS232 serial port, Ethernet, Bluetooth, WiFi (Bluetooth or WiFi)
CPU	32bit RISC MCP
Barcodes	ID: Code39,Code93,Codabar,Code128(Subsets A, B, and C), EAN-13,EAN-8,UPC-A,UPC-E,UPC/C/EAN Extensions, Planet Code, Standard 2 of 5,Industrial 2 of 5, Interleaved 2 of 5,LOGMARS, G51 Data Bar(RSS) 2D: PDF 417,MicroPDF417,QR Code,DataMatrix,MaxiCode, GSI Composite
Character enlargement/rotation	Rotate (0°, 90°, 180°, 270°) Enlarge (1-10x) Vector fonts support stepless scaling
Character set	Built in 7 dot matrix fonts and 1 vector font Support users to download dot matrix fonts and vector fonts
Graphical	Binary non-format bitmap, HEX, PCX, BMP and IMG can be download to FLASH, RAM
Paper type	Continuous paper, marking paper, label paper, perforated paper
Paper width	118mm (Max.)
Paper roll OD (Max.)	127mm(5 inch)
Paper roll ID	25.4mm(1 inch) /38mm(1.5 inch)
Paper out	Tear off/ Rewind/ Peel off (optional)/Cut (optional)
Paper thickness	0.06-0.25mm
Ribbon length	300m(Max.)
Ribbon ID	12.7mm/25.4mm
Button, Indicators	1 button,2 indicators
Input	100-240V AC, 50-60Hz
Output	24V DC, 2.5A
Operation conditions	5-45°C, 20 - 90%RH(40°C)
Storage conditions	-40-60°C, 20 - 93% RH(40°C)
Dimensions	280mm(L) x218mm(W)x180mm(H)
Weight	About 2.3kg