

# LP 46 Neo

## Desktop Barcode Label Printer

### CONVENIENCE

Movable black Mark Sensor  
Easy Operation  
Easy Maintenance

### TRUE VALUE

Dual Interface : USB + Serial  
Support : 1 inch & 0.5 inch -  
TTR Core



## SUPERIOR, FAST & AFFORDABLE

### High Printing Speed & High Reliability



### *Specification*

Printing Method	: Thermal Line Printing - Direct Thermal & Thermal Transfer
Resolution	: 203 dpi
Print Width	: 104 mm
Print Speed	: 150 mm (6")/second
CPU	: 32 bits/sec
Interface	: USB + Serial
Paper sensor	: Transmission sensor (Movable) Reflection sensor (Movable)
ID Barcode	: Code 3 of 9,UPCA,UPCE,interleaved 2 of 5,code 128,EAN 13,EAN 8,HBIC(39 code checkout),Codabar industry Code 25, storage and transportation code,UPC2,UPC5 Code 93,Postnet 25 (Chi na) ,UCC/EAN, matrix 25, etc
2D Barcode	: PDF417,MAXICODE,QR Code.etc
Paper type	: Marked paper, Black marked paper, Folding paper, Punched paper
Paper width	: 19-120mm
Paper thickness	: 0.06 - 0.20 mm
Paper roll OD	: Max.127mm
Paper roll ID	: 25/38mm
Ribbon ID	: 25.4 mm ; Width - max. 110 mm ; Length - max. 300 mm
Button light	: 1button - 2 lights
Input	: 110-240 V AC, 50/60 Mhz
Output	: 24 DC. 2.5A
Operation condition	: +5°C - 45°C ,20%-90%RH
Storage condition	: -40°C -60°C,20%-93%RH
Dimensions	: 210(W)*280(D)*185(H) mm
Weight	: About 2.1 Kgs

## FOR THE NEW AGE RETAILERS

- Superfast 6ips Speed
- Memory: 4 MB Flash, 8 MB SDRAM
- Interface: USB 2.0
- Print Head Life : 30 km
- Moveable Black Mark Sensor



Avail within 90 days of purchase