









Specification	
Printing Method	Thermal Line Printing
Print Width	72mm
Print Resolution	203 dpi
Print Speed	60mm/Sec
Interface	USB+Bluetooth 4.2
Paper Width	80mm (Receipt); Max3inch (76mm) (Label)
Ro II Diameter	Max.50mm
Paper Thickness	0.06-0.08mm
Barcode Type	UPC-A/JSN 13(EAN 13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE 93/CODE 128
	QR code
LED Screen	OLEDscreen, 30.4*14.5mm; Effective show size 25.58*6.38mm
Character	CodePage, GBK, UTF-8, Arabic, Unicode
Print Command	Compatible with ESC/POS(Receipt), TSPL(Label), CPCL(Waybill)
Character Size	12*24dots
Input Buffer	1.5K bytes
Power Adapter	Input AC220V; output DC9V/1A
Lithium Battery	2600 mAh/7.4V
Charging Time	3 hours
Stand-by Time	6~7 days
Print Head Life	50KM
Operating System	Android, IOS, Windows
Working temperature	0°C ~50°C; humidity 20%~85%
Storage temperature	-20 °C~60 °C, humidity 5%~95%
Product Size	12.5x11.5x6cm
Product Weight	500g
Drop specification	1.5m
IP rating	IP54
Operation switchs	Power, Feed, Setting
Working range	~100m
Memory capacity	RAM:512KB ROM:8MB